



VALVED SIAMESE

APPLIANCES

Valved Siamese

Used to combine several hoselines into one — usually at the fire scene — a Siamese must be both reliable and intuitive to use. All the Siamese are finished in red urethane enamel; the Elk-O-Lite® versions feature hard anodized trim and the brass versions offer chrome trim. As with all Elkhart products, years of dependable service are to be expected from an Elkhart Siamese.

4-5



Valve type determines available handle style from 3 options

INLETS	AVAILABLE OUTLETS		TYPE		HANDLE STYLE			VALVES		MATERIAL		DIMENSIONS		MODEL	FIGURE	
	Type	Size	1/4 Turn Ball Valve	X-86A Gate Valve	Crank	Self-Locking	Twist-Lock	Bleeder Valve .75"	Adjustable Relief Valve	Brass	Elk-O-Lite®	Length (Inches)	Weight (Lbs.)			
2.5" F (X2)	Female (Swivel)	2.5"	•				•	o		•	•	9.0	12.0	B-98A	1	
			•				•	o		•	•	9.0	30.5	B-98	1	
		3"	•				•	o			•	•	9.0	12.2	B-98A	1
			•				•	o			•	•	9.0	31.1	B-98	1
		3.5"	•				•	o			•	•	9.0	12.4	B-98A	1
			•				•	o			•	•	9.0	31.7	B-98	1
		4"	•				•	o			•	•	9.0	12.5	B-98A	1
	•					•	o			•	•	9.0	32.4	B-98	1	
	4.5"	•				•	o			•	•	9.0	13.0	B-98A	1	
		•				•	o			•	•	9.0	34.1	B-98	1	
	5"	•				•	o			•	•	9.0	13.6	B-98A	1	
		•				•	o			•	•	9.0	36.0	B-98	1	
	6"	•				•	o			•	•	9.0	14.5	B-98A	1	
		•				•	o			•	•	9.0	38.2	B-98	1	
Storz (Free Swivel)	4"	•		•	•			s		•	•	13.3	26.3	9722	3	
		•		•	•			s		•	•	12.8	24.3	9822		
5"	•				•					•	•	10.5	15.1	B-98A	1	
	•				•			s		•	•	13.3	26.3	9722	3	
								s		•	•	12.8	24.3	9822		
2.5" F (X3)	Female (Swivel)	2.5"	•				•	o		•	•	10.5	18.2	B-99A	2	
			•				•	o		•	•	10.5	45.5	B-99	2	
		3"	•				•	o			•	•	10.5	18.3	B-99A	2
			•				•	o			•	•	10.5	46.1	B-99	2
		3.5"	•				•	o			•	•	10.5	18.5	B-99A	2
			•				•	o			•	•	10.5	46.7	B-99	2
		4"	•				•	o			•	•	10.5	18.6	B-99A	2
	•					•	o			•	•	10.5	47.4	B-99	2	
	4.5"	•				•	o			•	•	10.5	19.2	B-99A	2	
		•				•	o			•	•	10.5	49.1	B-99	2	
	5"	•				•	o			•	•	10.5	19.7	B-99A	2	
		•				•	o			•	•	10.5	51.0	B-99	2	
	6"	•				•	o			•	•	10.5	20.7	B-99A	2	
		•				•	o			•	•	10.5	53.2	B-99	2	
Storz (Free Swivel)	4"	•		•	•			s		•	•	16.0	30.6	9723	4	
		•		•	•			s		•	•	15.0	27.7	9823	5	
	5"	•				•				•	•	10.5	21.2	B-99A	2	
								s		•	•	16.0	30.6	9723	4	
								s		•	•	15.0	27.7	9823	5	

KEY s = standard o = option



VALVED SIAMESE

FIGURE 1



B-98/B-98A

- Apparatus mountable
- Built-in strainer
- Adjustable neoprene seats

Fig. 1

FIGURE 2



B-99/B-99A

- Apparatus mountable
- Built-in strainer
- Adjustable neoprene seats

Fig. 2

FIGURE 3



9722

- Full, flow Hydro-Loc® valves
- Adjustable relief valve (75-250 psi)

Fig. 3

FIGURE 4



9723

- Full, flow Hydro-Loc® valves
- Adjustable relief valve (75-250 psi)

Fig. 4

FIGURE 5



9823

- Adjustable relief valve (75-250 psi)

Fig. 5

OPTIONS

THREADS

All fireground connections are NHT unless otherwise specified. See index T-13 for optional base threads.

ADDITIONAL INFORMATION

- All twist-locks feature metal knurled knobs.
- More Siamese options available. See page 4-3.