



## WHEELED FIRE EXTINGUISHER SPECIFICATIONS

| WHEELED EXTINGUISHER PHYSICAL ATTRIBUTES |          |                      |                       |                        |                       |                                     |                                   |
|--|----------|----------------------|-----------------------|------------------------|-----------------------|-------------------------------------|-----------------------------------|
| MODEL                                    | PART NO. | SHIPPING WT          | HEIGHT                | WIDTH                  | DEPTH                 | HOSE SIZE                           | WHEEL SIZE                        |
| A-50-SP                                  | 30010    | 193 lbs.             | 47 inches             | 24 inches              | 26.5 inches           | 25 ft. x .50 in                     | 12.3 x 3.5 in                     |
| K-50-SP                                  | 30030    | (88 kg)              | (119 cm)              | (61 cm)                | (67 cm)               | (7.6 m x 1.3 cm)                    | (31.3 x 8.9 cm)                   |
| A-150-SP                                 | 30110    | 343 lbs.             | 51 inches             | 26 inches              | 38 inches             | 50 ft x .75 in<br>(15.2 m x 1.9 cm) | 16 x 4 in<br>(40.6 x 10.2 cm)     |
| K-150-SP                                 | 30310    | (156 kg)             | (128 cm)              | (66 cm)                | (96.5 cm)             |                                     |                                   |
| A-150-RG                                 | 31120    | 413 lbs.             | 50 inches<br>(127 cm) | 24 inches<br>(61 cm)   | 42 inches<br>(105 cm) |                                     |                                   |
| K-150-RG                                 | 31320    | (188 kg)             |                       |                        |                       |                                     |                                   |
| S-150-RG                                 | 31220    | 438 lbs.<br>(199 kg) | 55 inches<br>(139 cm) | 32 inches<br>(81.3 cm) | 46 inches<br>(117 cm) |                                     | 36 x 2.5 in<br>(91.4 x 6.4 cm)    |
| A-150-RG                                 | 31140*   | 448 lbs.<br>(204 kg) |                       |                        |                       |                                     |                                   |
| A-150-RG                                 | 31150**  |                      |                       |                        |                       |                                     |                                   |
| K-150-RG                                 | 31340*   | 473 lbs.<br>(215 kg) |                       |                        |                       |                                     |                                   |
| K-150-RG                                 | 31350**  |                      |                       |                        |                       |                                     |                                   |
| S-150-RG                                 | 31240*   | 473 lbs.<br>(215 kg) | 50 inches<br>(127 cm) | 24 inches<br>(61 cm)   | 42 inches<br>(105 cm) |                                     | 16 x 4 in<br>(40.6 x 10.2 cm)     |
| S-150-RG                                 | 31250**  |                      |                       |                        |                       |                                     |                                   |
| A-150-PT                                 | 31110    | 345 lbs.             | 50 inches<br>(127 cm) | 24 inches<br>(61 cm)   | 42 inches<br>(105 cm) | 16 x 4 in<br>(40.6 x 10.2 cm)       |                                   |
| K-150-PT                                 | 31310    | (157 kg)             |                       |                        |                       |                                     |                                   |
| S-150-PT                                 | 31210    | 370 lbs.<br>(168 kg) |                       |                        |                       |                                     |                                   |
| A-350-RG                                 | 32120*   | 810 lbs.<br>(368 kg) | 58 inches<br>(147 cm) | 36 inches<br>(91.4 cm) | 48 inches<br>(122 cm) | 50 ft x 1 in<br>(15.2 m x 2.5 cm)   | 36 x 2.5 in<br>(91.4 x 6.4 cm)    |
| A-350-RG                                 | 32140**  |                      |                       |                        |                       |                                     |                                   |
| K-350-RG                                 | 32320*   |                      |                       |                        |                       |                                     |                                   |
| K-350-RG                                 | 32340**  |                      |                       |                        |                       |                                     |                                   |
| S-350-RG                                 | 32220*   | 860 lbs.<br>(391 kg) |                       |                        |                       |                                     | * Steel Wheels                    |
| S-350-RG                                 | 32240**  |                      |                       |                        |                       |                                     |                                   |
| A-350-PT                                 | 32110*   | 700 lbs.<br>(318 kg) |                       |                        |                       |                                     | ** Steel wheels with rubber tread |
| A-350-PT                                 | 32130**  |                      |                       |                        |                       |                                     |                                   |
| K-350-PT                                 | 32310*   |                      |                       |                        |                       |                                     |                                   |
| K-350-PT                                 | 32330**  | 750 lbs.<br>(341 kg) |                       |                        |                       |                                     |                                   |
| S-350-PT                                 | 32210*   |                      |                       |                        |                       |                                     |                                   |
| S-350-PT                                 | 32230**  |                      |                       |                        |                       |                                     |                                   |

| ABC WHEELED EXTINGUISHER PERFORMANCE SPECIFICATIONS |        |                     |            |                |                        |                |                 |
|---|--------|---------------------|------------|----------------|------------------------|----------------|-----------------|
| MODEL   | PART # | AGENT CAPACITY      | UL RATING  | DISCHARGE TIME | DISCHARGE RANGE        | OPERATING TEMP | USCG APPROVAL   |
| A-50-SP   | 30010  | 50 lbs. / 22.7 kg   | 30A-160B:C | 35 seconds     | 25-35 ft / 7.6-10.7 m  | -40 to 120 °F  | Type A Size II  |
| A-150-SP  | 30110  | 125 lbs.<br>56.7 kg | 40A-240B:C | 47 seconds     | 30-40 ft<br>9.1-12.2 m | -65 to 120 °F  | Type B:C Size V |
| A-150-RG  | 31120  |                     |            | -              |                        |                |                 |
| A-150-RG  | 31140  |                     |            | -              |                        |                |                 |
| A-150-RG  | 31150  |                     |            | -              |                        |                |                 |
| A-150-PT  | 31110  |                     |            | -              |                        |                |                 |
| A-150-PT  | 32120  | 300 lbs.<br>136 kg  | 40A-320B:C | 45 seconds     |                        |                | -               |
| A-350-RG  | 32140  |                     |            | 53 seconds     |                        |                | -               |
| A-350-RG  | 32110  |                     |            | 57 seconds     |                        |                | -               |
| A-350-PT  | 32130  |                     |            |                |                        |                | -               |

| PURPLE K WHEELED EXTINGUISHER PERFORMANCE SPECIFICATIONS |        |                     |           |                |                        |                |                 |
|--|--------|---------------------|-----------|----------------|------------------------|----------------|-----------------|
| MODEL  | PART # | AGENT CAPACITY      | UL RATING | DISCHARGE TIME | DISCHARGE RANGE        | OPERATING TEMP | USCG APPROVAL   |
| K-50-SP  | 30030  | 50 lbs. / 22.7 kg   | 160 B:C   | 34 seconds     | 25-35 ft / 7.6-10.7 m  | -40 to 120 °F  | Type B:C Size V |
| K-150-SP   | 30310  | 125 lbs.<br>56.7 kg | 320B:C    | 54 seconds     | 30-40 ft<br>9.1-12.2 m | -65 to 120 °F  | -               |
| K-150-RG   | 31320  |                     |           | -              |                        |                |                 |
| K-150-RG   | 31340  |                     |           | -              |                        |                |                 |
| K-150-RG   | 31350  |                     |           | -              |                        |                |                 |
| K-150-PT   | 31310  |                     |           | -              |                        |                |                 |
| K-150-PT   | 32320  | 300 lbs.<br>136 kg  |           | 54 seconds     |                        |                | -               |
| K-350-RG   | 32340  |                     |           | 56 seconds     |                        |                | -               |
| K-350-RG   | 32310  |                     |           | 58 seconds     |                        |                | -               |
| K-350-PT   | 32330  |                     |           |                |                        |                | -               |

| STANDARD WHEELED EXTINGUISHER PERFORMANCE SPECIFICATIONS |        |                    |           |                |                        |                |                 |
|--|--------|--------------------|-----------|----------------|------------------------|----------------|-----------------|
| MODEL  | PART # | AGENT CAPACITY     | UL RATING | DISCHARGE TIME | DISCHARGE RANGE        | OPERATING TEMP | USCG APPROVAL   |
| S-150-RG   | 31220  | 150 lbs.<br>68 kg  | 240B:C    | 48 seconds     | 30-40 ft<br>9.1-12.2 m | -65 to 120 °F  | -               |
| S-150-RG   | 31240  |                    |           |                |                        |                | -               |
| S-150-RG   | 31250  |                    |           |                |                        |                | -               |
| S-150-PT   | 31210  | 350 lbs.<br>159 kg | 320B:C    | 43 seconds     |                        |                | Type B:C Size V |
| S-350-RG   | 32220  |                    |           | 59 seconds     |                        |                | -               |
| S-350-RG   | 32240  |                    |           | 50 seconds     |                        |                | -               |
| S-350-PT   | 32210  |                    |           |                |                        |                | -               |
| S-350-PT   | 32230  |                    |           |                |                        |                | -               |